



System 60 Vario 1-70

SKU: 6085

Sachtler Video 60 Studio on Vario Ped
1-70

PRODUCT DESCRIPTION

When working with heavier cameras in studio or on location, being able to work quickly, effectively and safely gives you more time to get the best results. The Video 60 Studio fluid head's 18-step counterbalance system allows you to achieve perfectly adjusted balance quickly and simply. The sliding balance plate has a range of up to 115 mm / 4.5 in, giving you even more precise adjustment and safety at any angle. All while supporting a maximum payload of 65 kg. The Touch & Go quick release and automatic locking reduce mounting and releasing your camera to a matter of seconds. Once you are set and ready to go, the frictionless leak proof fluid drag with nine levels of drag gives you perfectly smooth movement both vertically and horizontally. The Video 60 has easily identifiable, direct response horizontal and vertical brakes that are vibration free. The integrated assembly lock lets you mount the camera safely. Whatever your schedule, the Sachtler Video 60 Plus Studio won't slow you down.

Highly stable and yet lightweight, the Vario pedestals provide optimum support both in Studio and OB environments. The Vario 1-70 is a robust, reliable and portable solution that provides soft and precise movement delivering unparalleled talent tracking and able to achieve seated and standing eyeline positions even at close range. The Vario Ped 1-70 features ergonomically positioned controls offering crab & steer functionality and can be used with payloads up to 70 kg / 154 lb. It has 2 stages, the upper stage is perfectly balanced for on shot performance. The lower stage is a balance assisted stage for easy elevation and extended height range. It has an integral manual pump and an inlet valve for use with an external source. In addition, the Vario Ped 1-70 includes a pressure gauge for clear and reliable set-up. The detachable dolly allows the

pedestal to be simply broken down into two sections for easy storage and transportation. It comes with 12.5cm / 5 inch wheels and adjustable cable guards. It also features narrow tracking and transit widths to allow for movement in tight spaces.

TECHNICAL SPECIFICATIONS

Payload	58 kg to 127.87 lb to
Counterbalance	18 steps
Drag	9 + 0 horizontal and vertical grades of drag
Weight	50.6 kg 111.55 lb
Bowl Size	Flat Base
Pan Bar Count	2 x pan bar from section
Sliding Range	12 cm 4.72 in
Tilt Range	90° to -60°
Interface Compatibility	V-plate
Stages	2
Perfect Balance Stages	1
On Shot Stroke	41 cm 16.14 in
Steering	Crab & Steer
Height For Pedestals	90 cm to 171 cm 35.43 in to 67.32 in

IN THE BOX

Vario Ped 1-70 incl Manual Pump and Video 60 Studio

- [Vario Ped 1-70](#) (S2302-0001)
- [Video 60 Plus Studio](#) (6001)
- [Manual Pump for Vario Ped 1-70 and Vario Ped 2-80](#) (V4172-1900)

YOU MAY ALSO LIKE...



System 60 Vario 2-80