



System FSB 6 75/2 AL GS Mk II

SKU: 0481A

- FSB 6 system with 2-stage aluminium tripod
- Smooth operation Create precision pans with smooth starts and soft stops
- Finely balanced Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg
- Always on the level - Innovative illuminated PrismBubble visible from any height – day or night
- Built for endurance - Engineered to the highest standards with tough materials and precision components
- Ground spreader, carry handle and padded bag included



PRODUCT DESCRIPTION

Fluid, Smooth, Balanced: Capture the moment precisely

Redesigned with features from the revolutionary Sachtler aktiv fluid head range, FSB delivers precision movement with finely calibrated levels of drag and counterbalance for the perfect shot. The streamlined profile is built to withstand the toughest conditions to deliver repeatable, reliable camera support shot after shot.

The FSB 6 features Speedbalance technology to finely balance any camera payload from 0kg up to 8kg (17.6lbs). The snap and go side loading mechanism with a sliding range of 120mm (4.7in) makes mounting and positioning accessorised cameras simple. An illuminated PrismBubble is visible from any height - day or night - to help ensure your setup is level.

Create precision pans with smooth starts and soft stops. Patented Sachtler drag always gives you subtle and smooth movement. Three horizontal and vertical drag settings help you to tune the drag to your payload.

The System includes a lightweight 2-stage aluminium 75mm tripod that's portable without sacrificing strength. With three 3/8" accessory mounting points on the tripod bowl you can add extra accessories like a Magic Arm and attach the included carry handle to help move the system around one-handed. The detachable ground spreader provides maximum stability, and a padded bag is included for transportation.

Engineered to the highest standards with tough materials and precision components, FSB is built for endurance. With no variation in performance in the widest range of temperatures and environments, FSB is the first choice for busy operators.

TECHNICAL SPECIFICATIONS

Weight	5.4 kg 11.9 lb
Height	59 cm to 175 cm 23.23 in to 68.9 in
Bowl Size	75 mm with integrated flat base
Material	Aluminium
Payload	0 kg to 8 kg 0 lb to 17.64 lb
Counterbalance	15 + 0 counterbalance steps
Drag	3 + 0 drag settings
Tripod Stages	2
Pan Bar Count	1
Sliding Range	12 cm 4.72 in
Tilt Range	90° to -70°
Temperature Range	-40 °C to 60 °C -40 °F to 140 °F
Transport Length	88 cm 34.65 in
Pan Bar Type	pan bar DV
Level Bubble	Yes, Prism Bubble
Camera Plate	Sideload

IN THE BOX

FSB 6 Mk II fluid head, tripod 75/2 AL Mk II, ground spreader SP 75, carry handle & padded bag 75

- [S2065-0001 - FSB 6 Mk II](#)
- [S2172-0001 - Tripod 75/2 AL Mk II](#)
- [7001 - Ground spreader SP 75](#)
- [S2051-1063 - Carry handle](#)
- [9116 - Padded bag 75](#)