



Vario Ped 2-80

SKU: S2303-0001

Fully steerable, 2-stage pedestal for payloads up to 80 kg / 176 lb



PRODUCT DESCRIPTION

Highly stable and yet lightweight, the Vario pedestals provide optimum support both in Studio and OB environments.

The functions of the Vario Ped 2-80 are perfectly matched to the requirements of Studio and OB daily life as it is a robust, reliable and protable solution that provides soft and precise movement delivering unparraled talent tracking and able to achieve seated and standing eyeline positions even at close range. It is a 2-stage pedestal for large payloads up to 80 kg / 176 lb in Studio and OB environment. Its smooth and precise on-air movement and on shot stroke length of 77cm / 30.3 in is perfect for following talent moving from seated to standing postion 'on shot'. It has an inlet valve for any air source and a pressure gauge for clear and reliable set-up.

The detachable skid allows the pedestal to be simply broken down into two sections for easy storage and transportation. The Vario Ped 2-80 has crab and steer functionality, allowing working in tight spaces and on shot direction changes. It comes with 12.5 cm / 5 inch wheels and adjustable cable guards.

The skid has an easy to adjust position for narrow clearance. The steering wheel has easily accessible slots for trim weights, which can be used to quickly adjust the column pressure if the temperature changes during the shot.



TECHNICAL SPECIFICATIONS

Payload	80 kg to 176.37 lb to
Steering Ring Diameter	63.5 cm 25 in
Wheel Diameter	12.5 cm 4.92 in
Narrow Transit Width	73 cm 28.74 in
Weight	44.4 kg 97.88 lb
Stages	2
Perfect Balance Stages	2
On Shot Stroke	77 cm 30.31 in
Steering	Crab & Steer
Height	66 cm to 143 cm 25.98 in to 56.3 in
Tracking Width	97 cm 38.19 in

IN THE BOX

- <u>S2303-0001 Vario Ped 2-80</u>
- <u>3357-21 Manual Portable Pump</u>

YOU MAY ALSO LIKE...









System 25 Vario 2-80

System 60 Vario 2-80 Vid

<u>Video 60 Plus Studio</u>

Video 75 Plus Studio