

aktiv12T



Level up with aktiv the fluid head built for speed.

When you have just one chance to capture the perfect shot, mount, level and lock the revolutionary aktiv™ fluid head in seconds.

Sachtler's unique SpeedLevel™ and SpeedSwap™ technologies deliver the fastest way to place and position your camera; adjust the level in an instant without ever taking your eye off the action; get closer to the ground than ever before for extreme low-angle shots or swap between a tripod, slider, or hand held without missing a beat. Capture the widest range of shots in the shortest time with aktiv™.

- Level and lock your head in an instant without missing a second of action. Unique SpeedLevel™ technology.
- Visible from any height or angle day or night. Innovative PrismBubble.
- Capture extreme low angle shots right down to the ground. Innovative streamlined mounting system.
- Switch between tripod and slider in seconds. Revolutionary SpeedSwap™ system.
- Create moving stories, whatever the weather. Performance tested to the extreme.
- Touch & Go quick release system. Simply drop the camera plate into the base the Touch & Go mechanism locks automatically. Pull the lever to remove your camera in an instant.

aktiv/27 52074T

aktiv™12T Touch & Go fluid head with SpeedLevel™ technology

Bowl size: 100 mm with SpeedSwap™ base Payload Range: 0-14 kg / 0-30.9 lb

Counterbalance steps: 15+0 Drag setting: 7+0

Weight: 3.3 kg / 7.3 lb Level: Illuminated PrismBubble Camera fitting: Touch & Go 16 Sliding range: 70 mm / 2.8 in Tilt range: +90° to -70° Temperature range:

-40°C to +60°C / -40°F to +140°F





Built for Speed.

Level up and lock your head in an instant.

Unique SpeedLevel[™] technology

Never miss the shot. aktivTM fluid heads feature revolutionary Speed-LevelTM technology. Release, level, and lock your head tightly into the perfect position without missing a second of action.



Visible from any height or angle - day or night.

Innovative PrismBubble

Clear confirmation that the camera is level comes from the illuminated PrismBubble visible from any height or angle – day or night.



Capture extreme low-angle shots right down to the ground.

Innovative streamlined mounting system

Go lower than ever. $aktiv^{TM}$ and flowtech® combine to provide a flexible one tripod solution delivering the widest height range. With no bowl clamp required, $aktiv^{TM}$ heads allow flowtech® tripods to go flat to the ground for the perfect low-angle shot.



Switch between tripod and slider in seconds.

Revolutionary SpeedSwap™ system

Stay fast for ultimate creativity. aktivTM fluid heads feature the unique SpeedSwapTM system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera movement is just a SpeedSwapTM awau.









System aktiv12T flowtech100 GS

System aktiv12T flowtech100 MS

	320/41-1103	320/41-611/13
Spreader type	Ground spreader	Mid-level spreader
Bowl	100 mm with SpeedSwap™	100 mm with SpeedSwap™
Payload range	0 - 14 kg / 0 - 30.9 lb	0 - 14 kg / 0 - 30.9 lb
Counterbalance steps	15+0	15+0
Drag setting	7+0	7+0
Balance range	70 mm / 2.8 in	70 mm / 2.8 in
Tilt range	+90° to -70°	+90° to -70°
Camera fitting	Touch & Go 16	Touch & Go 16
System weight	7.3 kg / 16.1 lb	7.4 kg / 16.3 lb
Height range with spreader	60 - 176 cm / 23.6 - 69.3 in	71 - 172 cm / 27.9 - 67.7 in
Height range without spreader	23 - 170 cm / 9 - 66.9 in	23 - 170 cm / 9 - 66.9 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in
Tripod stages	2	2
Tripod material	Carbon fibre	Carbon fibre

Combine the world's fastest tripod and the fluid head built for speed to record every second of action without missing a beat. aktiv flowtech systems are the perfect one tripod solution to capture the widest range of shots in the shortest time including extreme low-angle shots, closer to the ground than ever.