aktiv6



When you have just one chance to capture the perfect shot, mount, level and lock the revolutionary aktiv[™] fluid head in seconds.

Sachtler's unique SpeedLevel[™] and SpeedSwap[™] technologies deliver the fastest way to place and position your camera; adjust the level in an instant without ever taking your eye off the action; get closer to the ground than ever before for extreme low-angle shots or swap between a tripod, slider, or hand held without missing a beat. Capture the widest range of shots in the shortest time with aktiv[™].

- Level and lock your head in an instant without missing a second of action. Unique SpeedLevel[™] technology.
- Visible from any height or angle day or night. Innovative PrismBubble.
- Capture extreme low angle shots right down to the ground.
 Innovative streamlined mounting system.
- Switch between tripod and slider in seconds. Revolutionary SpeedSwap[™] system.
- Create moving stories, whatever the weather. Performance tested to the extreme.



aktiv 520645

aktiv™6 fluid head with SpeedLevel™ technology

Bowl size: 75 mm with SpeedSwap[™] base Payload Range: 0 - 8 kg / 0 - 17.6 lb Counterbalance steps: 15+0 Drag setting: 3+0 Weight: 2.6 kg / 5.7 lb Level: Illuminated PrismBubble Camera fitting: Sideload plate S Sliding range: 120 mm / 4.7 in Tilt range: +90° to -70° Temperature range: -40°C to +60°C / -40°F to +140°F

Built for **Speed**.

Level up and lock your head in an instant. Unique SpeedLevel[™] technology.

Never miss the shot. aktivTM fluid heads feature revolutionary Speed-LevelTM technology. Release, level, and lock your head tightly into the perfect position without missing a second of action.

Visible from any height or angle - day or night.

Clear confirmation that the camera is level comes from the illuminated PrismBubble visible from any height or angle – day or night.

Capture extreme low-angle shots right down to the ground.

Innovative streamlined mounting system.

Go lower than ever. aktiv[™] and flowtech® combine to provide a flexible one tripod solution delivering the widest height range. With no bowl clamp required, aktiv[™] heads allow flowtech® tripods to go flat to the ground for the perfect low-angle shot.

Switch between tripod and slider in seconds.

Revolutionary SpeedSwap™ system.

Stay fast for ultimate creativity. aktiv[™] fluid heads feature the unique SpeedSwap[™] system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera movement is just a SpeedSwap[™] away.







	System aktiv6 flowtech75 GS S2064S-FTGS	System aktiv6 flowtech75 MS S2064S-FTMS
Spreader type	Ground spreader	Mid-level spreader
Bowl	75 mm with SpeedSwap™	75 mm with SpeedSwap™
Payload range	0 - 8 kg / 0 - 17.6 lb	0 - 8 kg / 0 - 17.6 lb
Counterbalance steps	15+0	15+0
Drag setting	3+0	3+0
Sliding range	120 mm / 4.7 in	120 mm / 4.7 in
Tilt range	+90° to -70°	+90° to -70°
Camera fitting	Sideload S	Sideload S
System weight	6.4 kg / 14.1 lb	6.2 kg / 13.7 lb
Height range with spreader	56 - 176 cm / 22 - 69.3 in	79 - 174 cm / 31 - 68.5 in
Height range without spreader	23 - 170 cm / 9 - 66.9 in	23 - 170 cm / 9 - 66.9 in
Transport length	85 cm / 33.5 in	85 cm / 33.5 in
Tripod stages	2	2
Tripod material	Carbon fibre	Carbon fibre

Combine the world's fastest tripod and the fluid head built for speed to record every second of action without missing a beat. aktiv flowtech systems are the perfect one tripod solution to capture the widest range of shots in the shortest time including extreme low-angle shots, closer to the ground than ever.