aktiv87



Level up with aktiv[™] the fluid head built for speed.

When you have just one chance to capture the perfect shot, mount, level and lock the revolutionary aktiv[™] fluid head in seconds.

Sachtler's unique SpeedLevel[™] and SpeedSwap[™] technologies deliver the fastest way to place and position your camera; adjust the level in an instant without ever taking your eye off the action; get closer to the ground than ever before for extreme low-angle shots or swap between a tripod, slider, or hand held without missing a beat. Capture the widest range of shots in the shortest time with aktiv[™].

- Level and lock your head in an instant without missing a second of action. Unique SpeedLevel™ technology.
- Visible from any height or angle day or night. Innovative PrismBubble.
- Capture extreme low angle shots right down to the ground.
 Innovative streamlined mounting system.
- Switch between tripod and slider in seconds. Revolutionary SpeedSwap[™] system.
- Create moving stories, whatever the weather. Performance tested to the extreme.
- Touch & Go quick release system. Simply drop the camera plate into the base the Touch & Go mechanism locks automatically. Pull the lever to remove your camera in an instant.



aktiv87 52068T

aktiv™ST Touch & Go fluid head with SpeedLevel™ technology

Bowl size: 75 mm with SpeedSwap[™] base Payload Range: 0 - 12 kg / 0 - 26.5 lb Counterbalance steps: 15+0 Drag setting: 7+0 Weight: 2.8 kg / 6.2 lb Level: Illuminated PrismBubble Camera fitting: Touch & Go plate S Sliding range: 60 mm / 2.4 in Tilt range: +90° to -70° Temperature range: -40°C to +60°C / -40°F to +140°F

Built for **Speed**.

Level up and lock your head in an instant.

Never miss the shot. aktiv™ fluid heads feature revolutionary Speed-Level™ technology. Release, level, and lock your head tightly into the perfect position without missing a second of action.

Visible from any height or angle - day or night.

illuminated PrismBubble visible from any height or angle – day or night.

Capture extreme low-angle shots right down to the ground.

Go lower than ever. aktivTM and flowtech® combine to provide a flexible one tripod solution delivering the widest height range. With no bowl clamp required, aktiv™ heads allow flowtech® tripods to go flat to the ground for the perfect low-angle shot.

Switch between tripod and slider in seconds.

Stay fast for ultimate creativity. aktiv™ fluid heads feature the unique SpeedSwap™ system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera





	System aktiv8T flowtech75 GS S2068T-FTGS	System aktiv8T flowtech75 MS S2068T-FTMS
Spreader type	Ground spreader	Mid-level spreader
Bowl	75 mm with SpeedSwap™	75 mm with SpeedSwap™
Payload range	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb
Counterbalance steps	15+0	15+0
Drag setting	7+0	7+0
Sliding range	60 mm / 2.4 in	60 mm / 2.4 in
Tilt range	+90° to -70°	+90° to -70°
Camera fitting	Touch & Go plate S	Touch & Go plate S
System weight	6.6 kg / 14.5 lb	6.4 kg / 14.1 lb
Height range with spreader	56 - 176 cm / 22 - 69.3 in	79 - 174 cm / 31.1 - 68.5 in
Height range without spreader	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in
Transport length	85 cm / 33.5 in	85 cm / 33.5 in
Tripod stages	2	2
Tripod material	Carbon fibre	Carbon fibre







