



FSB 6 *Mk II*



Fluid, Smooth, Balanced

Capture the moment precisely

Redesigned with features from the revolutionary Sachtler aktiv fluid head range, FSB delivers precision movement with finely calibrated levels of drag and counterbalance for the perfect shot. The streamlined profile is built to withstand the toughest conditions to deliver repeatable, reliable camera support shot after shot.


- **Smooth operation.**
Create precision pans with smooth starts and soft stops.
- **Finely balanced.**
Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg.
- **Always on the level.**
Innovative illuminated PrismBubble visible from any height – day or night.
- **Built for endurance**
Engineered to the highest standards with tough materials and precision components.



FSB 6 *Mk II* S2065-0001

Bowl size: 75 mm with integrated flat base
Payload Range: 0 - 8 kg / 0 - 17.6 lb
Counterbalance steps: 15+0
Drag setting: 3+0
Camera fitting: Sideload S
Weight: 2.5 kg / 5.5 lb

Level: Illuminated PrismBubble
Sliding range: 120 mm / 4.7 in
Tilt range: +90° to -70°
Temperature range:
-40°C to +60°C / -40°F to +140°F





Fluid, Smooth, Balanced

1 Smooth operation.

Create precision pans with smooth starts and soft stops. The drag system delivers consistently smooth camera movements, fine-tuned to your payload.

2 Finely balanced.

Steady shots are standard with FSB. Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg, the widest range of cameras can be finely balanced in the perfect position.

3 Always on the level.

Instant confirmation that the camera is level comes from the innovative illuminated PrismBubble visible from any height – day or night.

4 Built for endurance.

Engineered to the highest standards with tough materials and precision components, FSB is built for endurance. With no variation in performance in the widest range of temperatures and environments, FSB is the first choice for outdoor operators.



FSB 6 Mk II



**System FSB 6 Mk II
75/2 AL GS**
0471AM



**System FSB 6 Mk II
75/2 CF GS**
0471CM



**System FSB 6 Mk II
75/2 AL MS**
0473AM



**System FSB 6 Mk II
75/2 CF MS**
0473CM

Spreader type	Ground spreader	Ground spreader	Mid-level spreader	Mid-level spreader
Bowl	75 mm	75 mm	75 mm	75 mm
Payload range	0 - 8 kg / 0 - 17.6 lb	0 - 8 kg / 0 - 17.6 lb	0 - 8 kg / 0 - 17.6 lb	0 - 8 kg / 0 - 17.6 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	3+0	3+0	3+0	3+0
Balance range	120 mm / 4.7 in	120 mm / 4.7 in	120 mm / 4.7 in	120 mm / 4.7 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°	+90° to -70°
Camera fitting	Sideload S	Sideload S	Sideload S	Sideload S
System weight	5.4 kg / 11.9 lb	4.9 kg / 10.8 lb	5.2 kg / 11.5 lb	4.7 kg / 10.4 lb
Height range with spreader	59 - 175 cm / 23.2 - 68.9 in	59 - 175 cm / 23.2 - 68.9 in	81 - 171 cm / 31.9 - 67.3 in	81 - 171 cm / 31.9 - 67.3 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in
Tripod stages	2	2	2	2
Tripod material	Aluminium	Carbon fibre	Aluminium	Carbon fibre